

Features and benefits



- World top class voltage series.
- Long term reliable cycle life
- Quick charge & discharge available


Typical Application

- HEV & FCEV
- Consumer application
- Short term UPS
- Windmill pitch control
- Power back up, voltage stabilizer
- Robotics memory back up



Physical properties

Dimension in mm (not to scale)



Specification

Rated Voltage	2.8 V	
Surge Voltage	3.0 V	
Capacitance Tolerance	-10% / 10%	
Resistance Tolerance	MAX.	
Operating temperature range	-40 ~ 65 °C	
Storage temperature range	-40 ~ 70 °C	
Life Time (25°C)	After 10 years at rated voltage and +25 °C	
	Capacitance change	Within 30% of initially specified value
	Internal resistance change	Within 100% of initially specified value
Cycle Life (25°C)	After 500,000 cycles between rated voltage to half rated voltage at +25 °C	
	Capacitance change	Within 30% of initially specified value
	Internal resistance change	Within 100% of initially specified value

Standard Ratings

Capacitance (F)	Dimension (mm)		Resistance(mΩ)		Continuous Current (A)	Max. Current (A)	Leakage Current (mA)	Max. Stored Energy (Wh)	Weight (g)	Part number
	D	L	(1kHz)	DC						
400	35	71	2.8	3	25	255	< 1	0.44	74	LSUC 002R8L 0400F EA
350	35	61	3	3.2	25	231	< 1	0.38	65	LSUC 002R8L 0350F EA

LS Ultracapacitors have been Certified by **ISO/TS16949, ISO14001:2004, OHSAS18001:2007, UL**

Design, Specifications may change without notice.

555, Hoge-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea, 431-831

Tel: 82-31-428-4545 Email: ultracapacitor@smtron.com

Copyright 2009 LS Mtron Ltd. All rights Reserved.